

## ANALOG BRUSHLESS PWM SERVO AMPLIFIERS AVAILABLE MOUNTING CONFIGURATIONS

<i>Electrical Ratings &amp; Available Mounting Configurations</i>					
Model Number	Brushless	Input Power	Output Power		Available Mounting Configurations
			Continuous Amps	Peak Amps	
SMA8X10LP	Brushless	70-240 VDC or 240-340 VDC	5	10	Module
		110-130 VAC or 208-240 VAC	5	10	Stand Alone and Multi-Axis
SMA8X10	Brushless	70-240 VDC or 240-340 VDC	10	20	Module
		110-130 VAC or 208-240 VAC	10	20	Stand Alone and Multi-Axis
SMA8X15	Brushless	70-240 VDC or 240-340 VDC	15	25	3U Plug-in and Module
		110-130 VAC or 208-240 VAC	15	25	Stand Alone and Multi-Axis
SMA8X15HP	Brushless	70-240 VDC or 240-340 VDC	20	40	3U Plug-in and Module
		110-130 VAC or 208-240 VAC	20	40	Stand Alone and Multi-Axis
SMA8X30-1A-1	Brushless	110-130 VAC or 208-240 VAC	30	60	Stand Alone
SMA8X075-1A-1	Brushless	110-130 VAC or 208-240 VAC	75	150	Stand Alone
SMA8X100-1A-1	Brushless	110-130 VAC or 208-240 VAC	100	150	Stand Alone